

# SP6

## Ultra compact two-way coaxial loudspeaker

### Features

- Passive two-way loudspeaker system with 1x6.5" coaxial transducer
- Subcompact enclosure
- High class transducers
- Integrated suspension system

### Technical Datasheet

---

|                                    |                |
|------------------------------------|----------------|
| Frequency Range (-10 dB):          | 90 Hz - 20 kHz |
| Max. SPL (Program power, 1 m):     | 122 dB SPL     |
| Power Handling (cont./prog./peak): | 300/600/1200 W |
| Nominal Impedance:                 | 8 Ohms         |
| Sensitivity (1W@1m):               | 95 dB          |
| Nominal coverage (H x V):          | 90° x 90°      |

### Components

---

|              |  |
|--------------|--|
| Transducers: | Coaxial 6.5" MF + 1.4" HF, neodymium         |
| Enclosure:   | Water resistant painted multilayered plywood |
| Termination: | Neutrik 4-pin Speakon                        |

### Physical

---

|                         |                          |
|-------------------------|--------------------------|
| Color:                  | Black or RAL-painted     |
| Dimensions (H x W x D): | 230 mm x 230 mm x 230 mm |
| Net Weight:             | 3.5 kg                   |

DiGiS Группа Компаний  
115230, Москва  
1-й Нагатинский проезд, д. 10 стр.1  
Тел.: (495) 787-8737  
info@digis.ru

[www.digis.ru](http://www.digis.ru)

**DI/AUDIO**